

# Arnystel 55

The Next Generation of Console-Mount Phones for Factories, Plants, Ships, Railways, Roads, Tunnels etc

The **ARNYSTEL 55** Series of Telephones are suitable for **airports**, **tunnels**, **ships**, **power stations**, **railways**, **roads**, **ships**, **public buildings**, **elevators & escalators**, **automatic barriers and many other applications**.

The **ARNYSTEL 55** is one of a range of specialised telephones and is manufactured by Arnesys to exacting standards.



#### They feature

- \* Heavy-duty construction
- \* Safety due to their non-metallic case & handset
- \* Corrosion resistance
- \* Solid State Electronics throughout
- \* Highly reliable operation & low cost of ownership
- \* Many options to suit your exact requirements

## **FEATURES**

#### The ARNYSTEL 55 features

- an attractive silver enclosure, which can be <u>console /wall or desk mounted</u>
- non-mechanical detection of the presence of the handset in its stowage
- a <u>very low Total Cost of Ownership</u> with a high MTBF, low MTTR due to its extremely rugged construction, advanced concepts and reliable components the ability to add a variety of LEDs, beacons or hooters etc
- electrical connections which may be brought in through the rear

#### **OPTIONS**

The **ARNYSTEL 55** can have a Headset instead of a Handset for extra noisy environments The **ARNYSTEL 55** can offer a variety of <u>Hooters/Sounders</u> and <u>beacons</u> for noisy areas The **ARNYSTEL 55** can have <u>Time Break Recall</u> or <u>Last Number Re-dial</u> keys The **ARNYSTEL 55** can have LED Ringing Indicator The **ARNYSTEL 55** can have <u>Stainless Steel Cord</u> to the handset. The **ARNYSTEL 55** can have a <u>Logo</u> to customer specifications The **ARNYSTEL 55** can be supplied in <u>other attractive colours</u> (consult factory)

### **Brief Specifications**

Enclosure Material	Heavy duty plastic, approx.3mm thick	
Dimensions overall	270mm high, 107mm wide, 50mm deep (including LP Handset)	
Weight	Approx. 1Kg. max. depending on options	
Temperature Range	-25 Deg.C to +60 Deg.C. min.	
Degree of Protection	IP54 (Optional with Rear Cover)	
<b>Relative Humidity</b>	to 95% non-condensing (Optional with Rear Cover)	
Cable Entries	Via rear entry	
Handset Body	Heavy duty plastic	
" Cord	Polyurethane Curly Cord (or Armoured Cable/Metal Spiral option)	
Keys (Keypad)	12 keys	(Arnystel 55-12)
	13/14 keys	(Arnystel 55-13 or 14) <b>OPTION</b>
(Hot Line / CB)	no keys required	(Arnystel 55-00) <b>OPTION</b>

# LAN-Phone 55 Low Profile Console Mount Telephone

270 mm

Front & Side Views