

Arnystel 220

The New Generation of Heavy Duty <u>Headset Telephones</u> for Ships, Machinery Rooms, Railways, Tunnels etc



The **ARNYSTEL 220** Series of Telephones are suitable for ships, airports, tunnels, power stations, railways, roads, machinery rooms, quarries and other extremely noisy environments. The **ARNYSTEL 220** is one of a range of specialised telephones and is manufactured by Arnesys to exacting standards. They feature

* Weathermoof and extremely reacting

- * Weatherproof and extremely rugged construction
- * Safety & Corrosion resistance due to their non-metallic case
- * Solid State Electronics throughout
- * Highly reliable operation & low cost of ownership
- * Many options to suit your exact requirements

The **ARNYSTEL 220** has been designed using the latest technology.

The **ARNYSTEL 220** is compatible with a wide range of networks ensuring clear speech quality at all times.

FEATURES

The ARNYSTEL 220 features

- an attractive yellow enclosure, which can be <u>wall/post or desk mounted</u>
 - a <u>very low Total Cost of Ownership</u> with a high MTBF and low MTTR due to its extremely rugged construction, advanced concepts and reliable components
- the ability to add a variety of beacons or hooters (Arnystel 221)
- electrical connections which may be brought in through a standard gland
- <u>non-mechanical</u> detection of the optional handset in its stowage

OPTIONS

The ARNYSTEL 220 can have a Handset as well as a Headset (Arnystel 240)
The ARNYSTEL 220 can offer a variety of <u>Hooters/Sounders</u> and beacons for extra noisy environments (Arnystel 221)
The ARNYSTEL 220 can have polyurethane <u>curly cord</u> to the headset.
The ARNYSTEL 220 can have a <u>Logo</u> to customer specifications
The ARNYSTEL 220 can be supplied in <u>other attractive colours</u> (consult factory)

Brief Specifications

Ditej specifications		
Enclosure Material	Heavy duty plastic, approx.3mm thick	
Dimensions overall	250mm high, 200mm wide, 120mm deep	
Weight	Approx. 1Kg. depending on options	
Temperature Range	-25 Deg.C to +60 Deg.C. min.	
Degree of Protection	IP65 (Typical)	
Relative Humidity	to 95% non-condensing	
Cable Entries	Drilled for M20 Glands (or PG7 option)	
Headset Body	Heavy duty plastic ear defenders	
" Cord	Polyurethane Cable (Curly Cord option)	
(Handset Body	Heavy duty plastic body sealed to a min of IP65	
" Cord	Armoured Cable/Metal Spiral)	
Keys (Keypad)	12 keys with "Ring Relay"	(Arnystel 221-12)
(Keypad)	12 keys	(Arnystel 220-12)
(Hot Line / CB)	no keys required with"Ring Relay"	(Arnystel 221-00)
(Hot Line / CB)	no keys required	(Arnystel 220-00)





